

Challenge for density ,  
Challenge for performance

SANYU/TPM surface mount reed relay provides various packages style and features from de-standard to application specified.



Vol. 2021.05

## ◆ 本期焦點



### 95D Series

- Contact Form : 1A / 2A / 3A / 1C(A+B)
- Coil Voltage : 5V / 12V / 24V
- **High Insulation Resistance up to  $10^{14}$**
- **Contact Rating Available in 10/50/100 Watt versions**
- **Lead Configuration in Lead and PCB**



### HY312HTS

- SOP 4 , 1 Form A solid state relay.
- Low driver current IF: 2mA/max(TTL/CMOS Compatible)
- Switch Load : 350mA & 60VAC or DC ~ max
- Low ON-Resistance : 0.13Ω / Typ.
- Input / Output isolation : 1500Vrms
- **Operating Temperature  $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$**



### TLP3450 貼片小型化

- VSON4 / Normally opened (1-Form-A)
- OFF-state output terminal voltage: 20 V (min)
- Trigger LED current: 3 mA (max)
- ON-state current: 200mA (max)
- ON-state resistance: 5 Ω (max), 3 Ω (typ.)
- **$C_{OFF} \times R_{ON} : 2.4$**

Challenge for density ,  
Challenge for performance

SANYU/TPM surface mount reed relay provides various packages style and features from de-standard to application specified.



## ◆ 賀！宜技科技通過ISO 9001：2015認證

宜技科技為確保提供客戶嚴格的品質管制以及標準化的業務流程，於2021年首次通過ISO 9001：2015品質管理系統國際驗證並取得證書。

